

**Features**

- Brass construction, 1/8 NPT and 1/4 NPT available with nickel plating;  
3.0 psi cracking pressure
- Plastic valve provided with Push-to-connect style fittings at no additional cost; new sizes\*  
0.5 psi cracking pressure
- Plastic valve now available in **Metric** sizes



Use in applications to control fluid in one direction. The free flow of the check valve is from port 1 to 2, the check function is from 2 to 1.



**Specifications**

Part Number	OAL	Stock Size	Connector	Working Pressure (psi)	Temp. Range	Materials
<b>PCCVA-02</b>	1.44	1/2	1/8 NPT	30 to 120	0° to +160°F	Brass/Nickel
<b>PCCVA-04</b>	1.85	11/16	1/4 NPT	30 to 120	0° to +160°F	Brass/Nickel
* <b>PCSCV-4</b>	1.80	.59	1/4 PI	230 max.	-20° to +185°F	Plastic
* <b>PCSCV-5</b>	1.85	.69	5/16 PI	230 max.	-20° to +185°F	Plastic
<b>PCSCV-6</b>	2.08	.78	3/8 PI	170 max.	-20° to +185°F	Plastic
* <b>PCSCV-8</b>	2.36	.91	1/2 PI	170 max.	-20° to +185°F	Plastic

\* Data is for air with nylon tubing- for other fluids or materials contact factory.

Please refer to page 54, **Plastic Push-in Fittings Specifications**, for working pressure/temperature range.

All measurements in inches unless otherwise specified

**Ordering Information**

**Check Valves**

Part No.	Connector	Pkg
<b>PCCVA-02</b>	1/8 NPT (F)	4
<b>PCCVA-04</b>	1/4 NPT (F)	4
<b>PCSCV-4</b>	1/4 PI	1
<b>PCSCV-5</b>	5/16 PI	1
<b>PCSCV-6</b>	3/8 PI	1
<b>PCSCV-8</b>	1/2 PI	1

- To order standard product use part number listing.
- Contact factory for optional seals.
- Contact factory for additional sizes.

