

## Features

- Clear, flexible and lightweight Vinyl tubing
- Complies with FDA requirements
- Full flow viewing ideal for handling beverages and liquids



Polyconn Polyvinylchloride tubing fitting recommendations: plastic or metal internal tube supports with outer sleeve or clamps.

## Specifications

Product	Temp. Range	Durometer
Polyvinylchloride	-20°F to +150° (higher temp. lower working pressure)	80 Shore "A"

Part Number	Pkg Unit Size	OD	ID	Working Pressure (psi) +70°F	Lbs./100'
PCPVC-125-0	100'	1/8	1/16	100	.5
PCPVC-250-0	100'	1/4	1/8	65	1.9
PCPVC-250-0-R	500'	1/4	1/8	65	1.9
PCPVC-312-0	100'	5/16	3/16	55	2.6
PCPVC-375-0	100'	3/8	1/4	50	3.2
PCPVC-437-0	100'	7/16	5/16	45	3.9
PCPVC-500-0	100'	1/2	3/8	40	4.5
PCPVC-562-0	100'	9/16	3/8	50	7.2
PCPVC-625-0	100'	5/8	3/8	60	10.3
PCPVC-750-0	100'	3/4	1/2	45	12.9

Measurements in inches unless otherwise noted

## Ordering Information

- Tubing is sold in package quantities, please refer to Specifications information for availability.
- Contact factory for special size or configuration.