

Sleeve Valves

Features

- Compact inline shut off valve ideal for supply control applications
- 3-Way function
- Five NPT sizes available



The valve opens by sliding the black anodized aluminum sleeve forward on the plated steel body. When the sleeve is in a closed position, two Buna-N O-rings ensure a leak proof seal and allow downstream flow to exhaust to atmosphere.

Specifications

Product	Working Pressure (psi)	Temp. Range	Media
Sleeve Valve	200	-65° to +250°F	Air and liquids compatible with materials of construction

Part Number	OAL	Hex	Connector Thd. (NPT)	C _v
PCSLV- 02	2-1/2	5/8	1/8	0.83
04	2-3/4	7/8	1/4	1.44
06	2-7/8	7/8	3/8	1.65
08	3-3/4	1-1/8	1/2	3.67
12	4	1-3/8	3/4	5.28

All measurements in inches unless otherwise specified

Ordering Information

Sleeve Operated Valves (Steel) 3-Way

Part No.	NPT (M)	NPT (F)	Pkg
PCSLV-02	1/8	1/8	1
PCSLV-04	1/4	1/4	1
PCSLV-06	3/8	3/8	1
PCSLV-08	1/2	1/2	1
PCSLV-12	3/4	3/4	1

■ To order standard product use part number listing.

■ All Sleeve valves are sold individually.

■ Contact factory for optional seals.